

CALIPER SPECIFICATIONS

ZR45

ZR45 Series Caliper

Two-piece - 4 piston - Removable Bridge - 2 Pad

Common Application: Various

Application	Rear	Rear	Front	Front
Mount Dim. (mm)	210 x 40.5	210 x 40.5	210 x 42	210 x 42
Piston sizes (mm)	29.0/36.5	29.0/36.5	36.5/41.0	41.0/44.0
Piston area per side (mm ²)	1706.86	1706.86	2366.6	2840.78
Max disc dia (mm)	355	355	355	355
Max disc thickness (mm)	32	32	35	35
Min disc thickness (mm)	28	28	31	31
Max pad thickness (mm)	21.5	21.5	21.5	21.5
Fluid capacity (cm ³)	54.6	54.6	75.7	90.9
Max operating pressure	103bar / 1500psi	103bar / 1500psi	103bar / 1500psi	103bar / 1500psi
Pad Shape	7852	7852	7852	7852
Pad area per side (cm ²)	57.05	57.05	57.05	57.05
Caliper weight	3.16kg / 7.0lbs	3.16kg / 7.0lbs	3.13kg / 6.9lbs	3.10kg / 6.8lbs

Handing	Caliper Part #	Caliper Part #	Caliper Part #	Caliper Part #
Leading Left	45.355.290.365.01	45.355.290.365.05	45.355.365.410.03	45.355.410.440.03
Leading Right	45.355.290.365.02	45.355.290.365.06	45.355.365.410.04	45.355.410.440.04
Trailing Left	45.355.290.365.11	45.355.290.365.15	45.355.365.410.13	45.355.410.440.13
Trailing Right	45.355.290.365.12	45.355.290.365.16	45.355.365.410.14	45.355.410.440.14

