

CALIPER SPECIFICATIONS

ZR54

ZR54 Series Caliper

Two Piece - 4 Piston - Removable Bridge - 2 Pad

Common Application: GT Front

Application	GT Front	GT Front	GT Front
Mount Dim. (mm)	210 x 35	210 x 35	210 x 35
Piston sizes (mm)	36.5/41.0	36.5/44.0	41.0/44.0
Piston area per side (mm ²)	2366.6	2566.92	2840.82
Max disc dia (mm)	378	378	378
Max disc thickness (mm)	32	32	32
Min disc thickness (mm)	30	30	30
Max pad thickness (mm)	29	29	29
Fluid capacity (cm ³)	68.6	74.46	82.47
Max operating pressure	103bar/1500psi	103bar/1500psi	103bar/1500psi
Pad shape	7836	7836	7836
Pad area per side (cm ²)	67.13	67.13	67.13
Caliper weight	3.90kg/8.6lbs	3.88kg/8.5lbs	3.90kg/8.6lbs

Handing	Caliper Part #	Caliper Part #	Caliper Part #
Leading Left	54.378.365.410.01	54.378.365.440.01	54.378.410.440.01
Leading Right	54.378.365.410.02	54.378.365.440.02	54.378.410.440.02
Trailing Left	54.378.365.410.11	54.378.365.440.11	54.378.410.440.11
Trailing Right	54.378.365.410.12	54.378.365.440.12	54.378.410.440.12

54 Series Caliper

Rotor OD(mm)	Pad Shape	Eff. Radius (mm)	'H' Dimm (mm)	'PL' Dimm (mm)
378	7836	105	124.2	66.7
362	7836	97	116.2	58.7
355	7836	93.5	112.7	55.2

STUD DIAMETER
MIN LOCATING: 11.975
MAX: 12.025

Pad Shape

See Pad comparison chart for thickness options and compound availability