

## CALIPER SPECIFICATIONS

### ZR62 Series Caliper Monobloc - 6 Piston - 2 Pad

# ZR62

Common Application: Z-Rated Street

Application	Z-Rated Street Front	Z-Rated Street Front
Mount dim. (mm)	285 x 32	285 x 32
Piston sizes (mm)	36.5/41.0/44.0	44.0/44.0/44.0
Piston area per side (mm <sup>2</sup> )	3887.1	4561.6
Max disc dia. (mm)	362	362
Max disc thickness (mm)	35	35
Min. disc thickness (mm)	28	28
Max pad thickness (mm)	15	15
Fluid Capacity (cm <sup>3</sup> )	77.7	91.2
Max operating pressure	103 bar / 1500 psi	103 bar / 1500 psi
Pad shape	7962	7962
Pad area per side (cm <sup>2</sup> )	84.65	84.65
Caliper weight	4.7kg/10.29lbs	4.7kg/10.29lbs

  

Handing	Caliper Part #	Caliper Part #
Leading Left	62.362.365.440.01	62.362.440.440.01
Leading Right	62.362.365.440.02	62.362.440.440.02
Trailing Left	62.362.365.440.11	62.362.440.440.11
Trailing Right	62.362.365.440.12	62.362.440.440.12

