

## CALIPER SPECIFICATIONS

# ZR18

### ZR18 Series Caliper Monobloc - 4 Piston - 2 Pad

Common Application: Short Track Front

Application	Short Track Front
Mount Dim. (mm)	180 x 42
Piston sizes (mm)	36.5/41.0
Piston area per side (mm <sup>2</sup> )	2366.6
Max disc dia (mm)	323
Max disc thickness (mm)	35
Min disc thickness (mm)	32
Max pad thickness (mm)	30
Fluid capacity (cm <sup>3</sup> )	113.6
Max operating pressure	103bar / 1500psi
Pad Shape	7821
Pad area per side (cm <sup>2</sup> )	72.14
Caliper weight	3.27kg / 7.2lbs

  

Handing	Caliper Part #
Leading Left	18.323.365.410.01
Leading Right	18.323.365.410.02
Trailing Left	18.323.365.410.11
Trailing Right	18.323.365.410.12

18.323.365.410.XX

Rotor OD (mm)	Pad Shape	Eff. Radius (mm)	'H' Dim (mm)	'PL' Dim (mm)
323.0	7821	132.5	105.0	56.5

Studs Diameter  
Min locating Ø: 11.975 mm  
Max Ø: 12.025 mm

See Pad comparison chart for thickness options and compound availability