

CALIPER SPECIFICATIONS
**ZR22 Series Caliper
Monobloc - 4 Piston - 2 Pad**
ZR22

Common Application: GT / Various

Application	Heavy Duty Rear	Intermediate Front	GT Rear	GT Front and Rear
Mount Dim. (mm)	180 x 42	180 x 42	180 x 42	180 x 42
Piston sizes (mm)	25.5/29.0	36.5/41.0	29.0/36.5	29.0/36.5
Piston area per side (mm ²)	1171.22	2366.6	1706.86	1706.86
Max disc dia (mm)	323	323	355	355
Max disc thickness (mm)	32	32	32	32
Min disc thickness (mm)	28	28	28	28
Max pad thickness (mm)	29	29	29	29
Fluid capacity (cm ³)	55.0	111.2	80.2	111.2
Max operating pressure	103bar / 1500psi	103bar / 1500psi	103bar / 1500psi	103bar / 1500psi
Pad Shape	7823	7823	7823	7823
Pad area per side (cm ²)	57.05	57.05	57.05	57.05
Caliper weight	2.61kg / 5.7lbs	2.57kg / 5.6lbs	2.61kg / 6.1lbs	2.57kg / 6.0lbs

Handing	Caliper Part #	Caliper Part #	Caliper Part #	Caliper Part #
Leading Left	22.323.255.290.01	22.323.365.410.01	22.355.290.365.01	22.355.365.410.01
Leading Right	22.323.255.290.02	22.323.365.410.02	22.355.290.365.02	22.355.365.410.02
Trailing Left		22.323.365.410.11	22.355.290.365.11	22.355.365.410.11
Trailing Right		22.323.365.410.12	22.355.290.365.12	22.355.365.410.12

