

## CALIPER SPECIFICATIONS

### ZR34 Series Caliper Monobloc - 4 Piston - 2 Pad

# ZR34

Common Application: Various

Application	Various	Various
Mount Dim. (mm)	180 x 42mm	180 x 42mm
Piston sizes (mm)	25.5/29.0	41.0/44.0
Piston area per side (mm <sup>2</sup> )	1171.22	2840.78
Max disc dia (mm)	330	330
Max disc thickness (mm)	32	32
Min disc thickness (mm)	30	30
Max pad thickness (mm)	19	19
Fluid capacity (cm <sup>3</sup> )	32.8	79.5
Max operating pressure	103bar / 1500psi	103bar / 1500psi
Pad Shape	7934 / 7823	7934 / 7823
Pad area per side (cm <sup>2</sup> )	74.8	74.8
Caliper weight	2.2kg / 4.9lbs	2.0kg / 4.5lbs

  

Handing	Caliper Part #	Caliper Part #
Leading Left	34.323.255.290.01	34.323.410.440.01
Leading Right	34.323.255.290.02	34.323.410.440.02
Trailing Left	34.323.255.290.11	34.323.410.440.11
Trailing Right	34.323.255.290.12	34.323.410.440.12

34.323.XXX.XXXX				
Rotor OD (mm)	Pad Shape	Eff. Radius (mm)	H' Dim (mm)	PL' Dim (mm)
323.0	7934	141.0	108.5	53.0
299.0	7934	129.0	96.5	53.0

#### Pad Shape

7934

7915

See Pad comparison chart for thickness options and compound availability

Slud Diameter  
Min localing : 11.975 mm  
Max : 12.025 mm