

CALIPER SPECIFICATIONS

ZR56

ZR56 Series Caliper Monobloc - 6 Piston - 2 Pad

Common Application: Z-Rated Street

| Application | Z-Rated Street | Z-Rated Street |
|---|--------------------|--------------------|
| Mount dim. (mm) | 285 x 37 | 285 x 37 |
| Piston sizes (mm) | 36.5/41.0/44.0 | 41.0/41.0/44.0 |
| Piston area per side (mm ²) | 3887.13 | 4361.316 |
| Max disc dia. (mm) | 405 | 405 |
| Max disc thickness (mm) | 36 | 36 |
| Min. disc thickness (mm) | 23 | 23 |
| Max pad thickness (mm) | 23.5 | 23.5 |
| Fluid Capacity (cm ³) | 99.12 | 111.21 |
| Max operating pressure | 103 bar / 1500 psi | 103 bar / 1500 psi |
| Pad shape | 7956 | 7956 |
| Pad area per side (cm ²) | 96.64 | 96.64 |
| Caliper weight | 11.75 lbs | 11.62 lbs |

| Handing | Caliper Part # | Caliper Part # |
|----------------|-------------------|-------------------|
| Leading Left | 56.405.365.440.01 | 56.405.410.440.01 |
| Leading Right | 56.405.365.440.02 | 56.405.410.440.02 |
| Trailing Left | 56.405.365.440.11 | 56.405.410.440.11 |
| Trailing Right | 56.405.365.440.12 | 56.405.410.440.12 |

Pad Shape

| 56.405.XXX.XXX.XX | | | | |
|-------------------|-----------|------------------|--------------|---------------|
| Rotor OD (mm) | Pad Shape | Elf. Radius (mm) | 'H' Dim (mm) | 'PL' Dim (mm) |
| 405.0 | 7956 | 170.75 | 121.4 | 81.1 |

Stud Diameter
Min Location ϕ : 11.975
Max ϕ : 12.025

See Pad comparison chart for thickness options and compound availability