

CALIPER SPECIFICATIONS
**ZR87 Series Caliper
Monobloc - 6 Piston**
ZR87

Common Application: Street Front

Application	Street Front	Street Front
Mount dim. (mm)	210 x 42	210 x 42
Piston sizes (mm)	29.0/32.0/36.5	25.5/29.0/32.0
Piston area per side (mm ²)	2511.11	1975.47
Max disc dia. (mm)	380	380
Max disc thickness (mm)	32	32
Min disc thickness (mm)	30	30
Max pad thickness (mm)	18	18
Fluid capacity (cm ³)	108.1	85.1
Max operating pressure	103bar/1500psi	103bar/1500psi
Pad shape	7987	7987
Pad area per side (cm ²)	82.68	82.68
Caliper weight	3.22kg/7.09lb	3.23kg/7.11lb

Handing	Caliper Part #	Caliper Part #
Leading Left	87.380.290.365.01	87.380.255.320.01
Leading Right	87.380.290.365.02	87.380.255.320.02
Trailing Left	87.380.290.365.11	87.380.255.320.11
Trailing Right	87.380.290.365.12	87.380.255.320.12

Rotor OD (mm)	Swept (mm)	Pad Shape	Eff. Radius (mm)	'H' Dim (mm)	'PL' Dim (mm)
380.0	55.0	7987	162.5	123.0	67.0
355.0	55.0	7987	160.0	110.5	67.0

Stud Diameter
 Min Locating Ø: 11.975mm
 Max Ø: 12.025mm

See Pad comparison chart for thickness options and compound availability