

CALIPER SPECIFICATIONS
ZR88 Series Caliper
Monobloc - 4 Piston
ZR88

Common Application: Street Front / Rear

Application	Front/Rear	Front/Rear	Front/Rear	Front/Rear	Front/Rear
Mount dim. (mm)	180 x 42	180 x 42	180 x 42	180 x 42	180 x 42
Piston sizes (mm)	41.0/44.0	36.5/41.0	32.0/36.5	29.0/32.0	25.5/29.0
Piston area per side (mm ²)	2840.8	2366.60	1850.59	1464.77	1171.23
Max disc dia. (mm)	355	355	355	355	355
Max disc thickness (mm)	30	30	30	30	30
Min disc thickness (mm)	28	28	28	28	28
Max pad thickness (mm)	18	18	18	18	18
Fluid capacity (cm ³)	110.8	92.4	72.2	57.2	45.8
Max operating pressure	103bar/1500psi	103bar/1500psi	103bar/1500psi	103bar/1500psi	103bar/1500psi
Pad shape	7988	7988	7988	7988	7988
Pad area per side (cm ²)	74.37	74.37	74.37	74.37	74.37
Caliper weight	2.84kg/6.27lb	2.84kg/6.27lb	2.83kg/6.25lb	2.83kg/6.25lb	2.82kg/6.22lb

Handing	Caliper Part #	Caliper Part #	Caliper Part #	Caliper Part #	Caliper Part #
Leading Left	88.355.410.440.01	88.355.365.410.01	88.355.320.365.01	88.355.290.320.01	88.355.255.290.01
Leading Right	88.355.410.440.02	88.355.365.410.02	88.355.320.365.02	88.355.290.320.02	88.355.255.290.02
Trailing Left	88.355.410.440.11	88.355.365.410.11	88.355.320.365.11	88.355.290.320.11	88.355.255.290.11
Trailing Right	88.355.410.440.12	88.355.365.410.12	88.355.320.365.12	88.355.290.320.12	88.355.255.290.12

88 Series Caliper

Rotor OD (mm)	Swept (mm)	Pad Shape	Eff. Radius (mm)	'H' Dim (mm)	'PL' Dim (mm)
355.0	55.0	7988	150.0	115.0	62.5
330.0	55.0	7988	137.5	102.5	62.5

See Pad comparison chart for thickness options and compound availability