



## Performance Friction RH665 DOT 4 Racing Brake Fluid



### IMPORTANT! HEALTH AND SAFETY INFORMATION

<b>Product:</b>	Performance Friction RH665 Dot 4 Racing Brake Fluid
<b>Description:</b>	Colourless to amber mobile liquid containing polyalkylene glycols and polyalkylene glycol ethers.
<b>Application</b>	Competition Brake Fluid

#### FIRST AID PROCEDURES

<b>Eyes</b>	Eye contact will cause irritation. Flush immediately with copious quantities of water for at least 10 minutes. Obtain medical attention.
<b>Skin</b>	Wash well with soap and water. Repeated and prolonged contact may give rise to skin disorder. Should this develop, obtain medical advice.
<b>Ingestion</b>	If a substantial quantity is ingested, obtain medical attention immediately.
<b>Aspiration</b>	Obtain medical attention immediately.
<b>Inhalation</b>	In the unlikely event of inhalation, remove from exposure and obtain medical attention

#### FIRE PROTECTION INFORMATION

<b>Flash Point (test method)</b>	145° C (Cleveland Open Cup) (NOT classified as highly flammable).
<b>Suitable Extinuising Media</b>	Any convenient means e.g. CO <sub>2</sub> dry powder, foam or water.
<b>Hazardous Decompostion / Combustion Products</b>	Irritant fumes. Breathing apparatus must be worn.

# IMPORTANT! HEALTH AND SAFETY INFORMATION

## SAFETY HANDLING ADVICE

### STORAGE

1. Avoid any contamination of this product by oil, petrol, solvents or water.
2. Store undercover in original sealed container.
3. Store below 50°C if possible to prevent pressurisation of container.

### HANDLING

1. Wear eye protection, impervious gloves and apron when transferring between containers.
2. Change any contaminated clothing immediately.
3. This product has a defatting action on the skin. Prolonged exposure may give rise to skin disorders. Apply a suitable barrier cream before use, and emollient cream after use.
4. Do not eat, drink or smoke whilst using this product.
5. Leakage from high pressure systems may result in mist formation. Ensure adequate ventilation.

### WARNING STATEMENT

No significant hazard when used in the application for which it was designed for. Harmful if swallowed in quantity. Mild eye and skin irritant.

### OCCUPATIONAL EXPOSURE LIMITS - EH 40 LISTED

8 Hour TWA	10 Minute TWA
Not Listed	Not Listed

### CONVEYANCE INFORMATION

UN / SI Number      Not classified as  
Classification      dangerous for conveyance  
Packing Group      by any means of transport  
CEPIC Tremcard No.      nationally or  
Hazchem Name      Internationally  
ITATA / IACO

### SUPPLY INFORMATION

Classification: Xi-Irritant  
Risk Phrases: R36 R52 R53  
Safety Phrases: S2 S26 S29 S46

### PROTECTION OF THE ENVIRONMENT

**Behaviour in water**      Miscible with water

**Spillage**      Prevent entry into drains, sewers and watercourses.  
Soak up with inert absorbent material.

**Waste Disposal**      Dispose of in can via an authorised contractor as  
oil-hazardous waste. EWC No. 16.01.13

### Performance Friction (UK) Ltd

Carbon Metallic House, Wildmere Road, Banbury Oxon OX16 3LU United Kingdom  
Tel: +44(0)1295 221020 Fax: +44(0)1295 279711

uksales@pfcbrakes.com  
www.pfcbrakes.com